



Eisenhour Church Furnishings

1137 Cleveland Rd. E. • P.O. Box 489 • Huron, OH 44839
1-800-686-0567 or 419-433-8071 • FAX 419-433-7559

#11 SOLID WOOD PEW SPECIFICATIONS

*WOOD SPECIES: Northern Red Oak FAS

Note: Veneer, particle board, and compression type boards are not acceptable.

*WOOD GLUE JOINTS: Adhesive used is Franklin Tight Bond.

*SANDING: All wood is machined and or hand sanded and polished before finishing to eliminate blemishes and give a professional finish.

*STAIN FINISH: Hand rubbed oil base stains. Light colors include filler stains.

*CLEAR COAT FINISH: Pre-catalyzed lacquer

*PEW END & SUPPORT LEGS: 2 ply solid wood construction, ends are 2" thick and support legs are 1 1/2" thick. Ends are available in 3 ply 2 1/4" thick construction.

*ANCHORS: Concealed anchors use (1) anchor in each end and all support legs.

*BOOKRACKS & CARD HOLDERS: Both are solid wood. Continuous bookracks are routed into ends and support legs for stronger attachment.

*WOOD SEATS & BACKS: Seats and backs are routed into ends. Seats are set on wood cleats. Seats are constructed using 5/4 lumber and backs using 4/4 lumber. Backs are routed into pew ends.

*WOOD BACKS OVER 16'-0" LONG: Backs are spliced together with 1 1/2" X 1/4" spline. Spline inserts 3/4" into each side within 1" of the complete back length and glued and stapled. A continuous solid wood cap-rail tongue and grooved is added to pews up to 24'-0" long.

*MITERED PEWS: Miters are installed with K & V T lock joint fasteners. Two are used under seats and two are used on backs. 1 1/2" mitered support leg is v-routed to fit miter and extend to bottom of cap-rail. Trim molding is added to each side of mitered support on backs.

*WARRANTY: For 20 years on glue joint separation and all structural joints, including pew ends and supports. See warranty sheet for complete details.